

Nanoparticles for Permeable reactive barriers: Production and application of mobile particles

Original

Nanoparticles for Permeable reactive barriers: Production and application of mobile particles / Mohammadian, Sadjad; Krok, Beate; SالدARRIAGA HERNANDEZ, LAURA ANDREA; Bianco, Carlo; Sethi, Rajandrea; Meckenstock, Rainer. - ELETTRONICO. - (2017), pp. 1-1. (Intervento presentato al convegno 9th International Conference on Porous Media & Annual Meeting tenutosi a Rotterdam nel 8-11 May 2017).

Availability:

This version is available at: 11583/2687674 since: 2017-10-26T13:36:46Z

Publisher:

Interpore

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Nanoparticles for Permeable reactive barriers: Production and application of mobile particles

Wed May 10, 2017

2:53 PM - 2:56 PM

Room 1

Description

Authors: Sadjad Mohammadian; Beate Krok; Laura Andrea Saldarriaga Hernandez; Carlo Bianco; Rajandrea Sethi; Rainer U. Meckenstock

Permeable reactive barriers have been recognized as a cost-effective technology for in-situ groundwater remediation. Placement of the barrier underground is the biggest challenge in this technology, consuming most of scientific and financial resources, so far. Injecting engineered nanoparticle suspensions to create a reactive barrier in soils has shown potential to overcome this challenge. Nanoparticles will deposit on aquifer sand, and then adsorb and/or react with groundwater contamination. Injection can be made using wellbores, thus reducing the costs of the barrier placement. However, nanoparticles have low mobility and are transformed (and thereby lose their capacity to react) in the close vicinity of the injection zone.

We have designed and produced Goethite nanoparticles to adsorb heavy metals in contaminated groundwater. Our colloidal suspensions show high stability and mobility in different sediment types. Laboratory tests with aquifer materials and numerical simulations were combined in order to understand how different hydrological and hydrogeochemical parameters affect the particle mobility when injected in porous media. The final nanoparticles are stable over days, facilitating transport from the place of production to the injection sites, and therefore minimizing on-site modification. By adjusting the concentrations of the injected suspensions and the injection flowrates, a desired mass of nanoparticles can travel in aquifers without accumulating near the wellbore or clogging pores. For example, a radius of influence of 4 meter was achieved at an injection rate of 60l/min. At such scale, the number of drilling and completion activities are lowered and stable, cost-effective reactive barriers can be placed. We thus present an applicable technology for the creation of in situ adsorption barriers for heavy metals in groundwater.